Medium-Large Payloads Robot



ER50-2100

ER50-2100 is a medium payloads robot.

Maxium payload 50 kg with maxium reach 2146 mm.

Highlights

Thanks to the high stiffness structure, with high-speed intelligent palletizing application software, the takt is improved by 20%, bring customers more efficiency;

Multiple specific application software could be integrated, with soft PLC and a variety of field bus interface, which enable customers easily face various application challenges;

High performance collision detection function helps safety realization.

Applications

It can be widely used in handling, polishing, palletizing, machine tending and other applications.

Industries

Suitable for auto parts, photovoltaic, food and beverage, building materials, logistics and warehousing and other industries.



EFORT INTELLIGENT EQUIPMENT CO.,LTD.

PHONE: (00 86) 400-052-8877

ADDRESS: No.96 East WanChun Road, JiuJiang Economic Development Zone, Wuhu, Anhui, China


WWW.EFORT.COM.CN

SPECIFICATIONS


Model		ER50-2100
Туре		Articulated
Controlled axes		6 Axes
Max payload at wrist		50 kg
Repeatability		± 0.06 mm
Robot weight		550 kg
Reach		2146 mm
Robot IP grade		IP54/IP67 (Wrist)
Cabinet IP grade		IP54
Drive mode		AC servo drive
Installation		Floor
Installation enviroment	Ambient temperature	0~45 ℃
	Ambient humidity	80% RH/40℃(No dew nor frost allowed)
	Vibration acceleration	4.9 m/s² (< 0.5 G)

Allowable load moment at wrist	J4	182 N·m
	J5	182 N·m
	J6	120 N·m
Allowable load inertia at wrist	J4	12.68 kg · m²
	J5	12.68 kg · m²
	J6	10 kg·m²
	J1	170°/sec
	J2	170°/sec
Maximum and	J3	170°/sec
Maximum speed	J4	270°/sec
	J5	270°/sec
	J6	365°/sec
	J1	± 180°
	J2	+70°/-130°
Na di un unun	J3	+175°/-80°
Motion range	J4	± 360°
	J5	± 115°
	J6	± 450°


OPERATING SPACE



BASE MOUNTING SIZE



END FLANGE MOUNTING SIZE



Information Release Time 2023/05